

< IGBT MODULES >

CM100DY-34A

HIGH POWER SWITCHING USE
INSULATED TYPE



Dual (Half-Bridge)

Collector current I_C **100 A**
 Collector-emitter voltage V_{CES} **1700 V**
 Maximum junction temperature T_{jmax} **150 °C**


- Flat base Type
- Copper base plate
- RoHS Directive compliant
- UL Recognized under UL1557, File E323585

APPLICATION

AC Motor Control, Motion/Servo Control, Power supply, etc.

OUTLINE DRAWING & INTERNAL CONNECTION


Dimension in mm



Tolerance otherwise specified

| Division of Dimension | Tolerance |
|-----------------------|-----------|
| 0.5 to 3 | ± 0.2 |
| over 3 to 6 | ± 0.3 |
| over 6 to 30 | ± 0.5 |
| over 30 to 120 | ± 0.8 |
| over 120 to 400 | ± 1.2 |

INTERNAL CONNECTION



< IGBT MODULES >

CM100DY-34A

HIGH POWER SWITCHING USE
INSULATED TYPE

ABSOLUTE MAXIMUM RATINGS (T_J=25 °C, unless otherwise specified)

| Symbol | Item | Conditions | Rating | Unit |
|---------------------------|---------------------------|---|------------|------|
| V _{CES} | Collector-emitter voltage | G-E short-circuited | 1700 | V |
| V _{GES} | Gate-emitter voltage | C-E short-circuited | ±20 | V |
| I _C | Collector current | DC, T _C =108 °C (Note.2, 4) | 100 | A |
| I _{CRM} | | Pulse, Repetitive (Note.3) | 200 | |
| P _{tot} | Total power dissipation | T _C =25 °C (Note.2, 4) | 960 | W |
| I _E (Note.1) | Emitter current | T _C =25 °C (Note.2, 4) | 100 | A |
| I _{ERM} (Note.1) | | Pulse, Repetitive (Note.3) | 200 | |
| T _J | Junction temperature | - | -40 ~ +150 | °C |
| T _{stg} | Storage temperature | - | -40 ~ +125 | |
| V _{isol} | Isolation voltage | Terminals to base plate, RMS, f=60 Hz, AC 1 min | 3500 | V |

ELECTRICAL CHARACTERISTICS (T_J=25 °C, unless otherwise specified)

| Symbol | Item | Conditions | Limits | | | Unit | |
|--------------------------|--------------------------------------|---|------------------------|------|------|------|---|
| | | | Min. | Typ. | Max. | | |
| I _{CES} | Collector-emitter cut-off current | V _{CE} =V _{CES} , G-E short-circuited | - | - | 1.0 | mA | |
| I _{GES} | Gate-emitter leakage current | V _{GE} =V _{GES} , C-E short-circuited | - | - | 2.0 | µA | |
| V _{GE(th)} | Gate-emitter threshold voltage | I _C =10 mA, V _{CE} =10 V | 5.5 | 7.0 | 8.5 | V | |
| V _{CEsat} | Collector-emitter saturation voltage | I _C =100 A (Note.5), V _{GE} =15 V | T _J =25 °C | - | 2.2 | 2.8 | V |
| | | | T _J =125 °C | - | 2.45 | - | |
| C _{ies} | Input capacitance | V _{CE} =10 V, G-E short-circuited | - | - | 24.7 | nF | |
| C _{oes} | Output capacitance | | - | - | 2.8 | | |
| C _{res} | Reverse transfer capacitance | | - | - | 0.53 | | |
| Q _G | Gate charge | V _{CC} =1000 V, I _C =100 A, V _{GE} =15 V | - | 670 | - | nC | |
| t _{d(on)} | Turn-on delay time | V _{CC} =1000 V, I _C =100 A, V _{GE} =±15 V, R _G =4.8 Ω, Inductive load | - | - | 200 | ns | |
| t _r | Rise time | | - | - | 150 | | |
| t _{d(off)} | Turn-off delay time | | - | - | 550 | | |
| t _f | Fall time | | - | - | 350 | | |
| V _{EC} (Note.1) | Emitter-collector voltage | I _E =100 A (Note.5), G-E short-circuited | - | 2.3 | 3.0 | V | |
| t _{rr} (Note.1) | Reverse recovery time | V _{CC} =1000 V, I _E =100 A, V _{GE} =±15 V, R _G =4.8 Ω, Inductive load | - | - | 300 | ns | |
| Q _{rr} (Note.1) | Reverse recovery charge | R _G =4.8 Ω, Inductive load | - | 10 | - | µC | |
| E _{on} | Turn-on switching energy per pulse | V _{CC} =1000 V, I _C =I _E =100 A, V _{GE} =±15 V, R _G =4.8 Ω, T _J =125 °C, | - | 21.3 | - | mJ | |
| E _{off} | Turn-off switching energy per pulse | Inductive load | - | 30 | - | | |
| E _{rr} (Note.1) | Reverse recovery energy per pulse | Inductive load | - | 33 | - | mJ | |
| r _g | Internal gate resistance | Per switch, T _c =25 °C | - | 0 | - | Ω | |

THERMAL RESISTANCE CHARACTERISTICS


| Symbol | Item | Conditions | Limits | | | Unit |
|-----------------------|-------------------------------------|---|--------|-------|------|------|
| | | | Min. | Typ. | Max. | |
| R _{th(j-c)Q} | Thermal resistance (Note.2) | Junction to case, per IGBT | - | - | 0.13 | K/W |
| R _{th(j-c)D} | | Junction to case, per FWDi | - | - | 0.21 | K/W |
| R _{th(c-s)} | Contact thermal resistance (Note.2) | Case to heat sink, per 1/2 module, Thermal grease applied (Note.6) | - | 0.022 | - | K/kW |

MECHANICAL CHARACTERISTICS

| Symbol | Item | Conditions | Limits | | | Unit |
|----------------|------------------------|---------------------------------|--------|------|------|------|
| | | | Min. | Typ. | Max. | |
| M _t | Mounting torque | Main terminals M 5 screw | 2.5 | 3.0 | 3.5 | N·m |
| M _s | | Mounting to heat sink M 6 screw | 3.5 | 4.0 | 4.5 | N·m |
| m | Weight | - | - | 310 | - | g |
| e _c | Flatness of base plate | On the centerline X, Y (Note.7) | -100 | - | +100 | µm |

< IGBT MODULES >
CM100DY-34A
HIGH POWER SWITCHING USE
INSULATED TYPE

- Note1. Represent ratings and characteristics of the anti-parallel, emitter-collector free wheeling diode (FWDi).
 2. Case temperature (T_c) and heat sink temperature (T_s) are defined on the each surface (mounting side) of base plate and heat sink just under the chips. Refer to the figure of chip location.
 The heat sink thermal resistance should measure just under the chips.
 3. Pulse width and repetition rate should be such that the device junction temperature (T_j) dose not exceed T_{jmax} rating.
 4. Junction temperature (T_j) should not increase beyond T_{jmax} rating.
 5. Pulse width and repetition rate should be such as to cause negligible temperature rise. Refer to the figure of test circuit.
 6. Typical value is measured by using thermally conductive grease of $\lambda=0.9 \text{ W/(m}\cdot\text{K)}$.
 7. Base plate (mounting side) flatness measurement points (X, Y) are as follows of the following figure.




RECOMMENDED OPERATING CONDITIONS

| Symbol | Item | Conditions | Limits | | | Unit |
|------------|-------------------------------|------------------------------|--------|------|------|----------|
| | | | Min. | Typ. | Max. | |
| V_{CC} | (DC) Supply voltage | Applied across C1-E2 | - | 1000 | 1100 | V |
| V_{GEon} | Gate (-emitter drive) voltage | Applied across G1-Es1/G2-Es2 | 13.5 | 15.0 | 16.5 | V |
| R_G | External gate resistance | Per switch | 4.8 | - | 48 | Ω |


CHIP LOCATION (Top view)

Dimension in mm, tolerance: ± 1 mm




< IGBT MODULES >
CM100DY-34A
 HIGH POWER SWITCHING USE
 INSULATED TYPE

TEST CIRCUIT AND WAVEFORMS




V_{CEsat} test circuit


V_{EC} test circuit




Switching characteristics test circuit and waveforms




t_{rr} , Q_{rr} test waveform



IGBT Turn-on switching energy



IGBT Turn-off switching energy




FWDi Reverse recovery energy

Turn-on / Turn-off switching energy and Reverse recovery energy test waveforms (Integral time instruction drawing)


< IGBT MODULES >
CM100DY-34A
 HIGH POWER SWITCHING USE
 INSULATED TYPE

PERFORMANCE CURVES


OUTPUT CHARACTERISTICS
 (TYPICAL)




COLLECTOR-EMITTER SATURATION
 VOLTAGE CHARACTERISTICS
 (TYPICAL)



COLLECTOR-EMITTER SATURATION
 VOLTAGE CHARACTERISTICS
 (TYPICAL)



FREE WHEELING DIODE
 FORWARD CHARACTERISTICS
 (TYPICAL)




< IGBT MODULES >
CM100DY-34A
 HIGH POWER SWITCHING USE
 INSULATED TYPE

PERFORMANCE CURVES


**HALF-BRIDGE
 SWITCHING CHARACTERISTICS
 (TYPICAL)**

$V_{CC}=1000\text{ V}$, $V_{GE}=\pm 15\text{ V}$, $R_G=4.8\ \Omega$,
 $T_J=125\text{ }^\circ\text{C}$, INDUCTIVE LOAD




**HALF-BRIDGE
 SWITCHING CHARACTERISTICS
 (TYPICAL)**

$V_{CC}=1000\text{ V}$, $I_C=100\text{ A}$, $V_{GE}=\pm 15\text{ V}$,
 $T_J=125\text{ }^\circ\text{C}$, INDUCTIVE LOAD




**HALF-BRIDGE
 SWITCHING CHARACTERISTICS
 (TYPICAL)**

$V_{CC}=1000\text{ V}$, $V_{GE}=\pm 15\text{ V}$, $R_G=4.8\ \Omega$, $T_J=125\text{ }^\circ\text{C}$
 INDUCTIVE LOAD, PER PULSE



**HALF-BRIDGE
 SWITCHING CHARACTERISTICS
 (TYPICAL)**

$V_{CC}=1000\text{ V}$, $I_C/I_E=100\text{ A}$, $V_{GE}=\pm 15\text{ V}$, $T_J=125\text{ }^\circ\text{C}$
 INDUCTIVE LOAD, PER PULSE




< IGBT MODULES >
CM100DY-34A
 HIGH POWER SWITCHING USE
 INSULATED TYPE

PERFORMANCE CURVES


**CAPACITANCE CHARACTERISTICS
 (TYPICAL)**

G-E short-circuited, $T_j=25^\circ\text{C}$




**FREE WHEELING DIODE
 REVERSE RECOVERY CHARACTERISTICS
 (TYPICAL)**

$V_{CC}=1000\text{ V}$, $V_{GE}=\pm 15\text{ V}$, $R_G=4.8\ \Omega$,
 $T_j=25^\circ\text{C}$, INDUCTIVE LOAD




**GATE CHARGE CHARACTERISTICS
 (TYPICAL)**

$I_C=100\text{ A}$, $T_j=25^\circ\text{C}$



**TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS
 (MAXIMUM)**

Single pulse, $T_C=25^\circ\text{C}$
 $R_{th(j-c)Q}=0.13\text{ K/W}$, $R_{th(j-c)D}=0.21\text{ K/W}$



Important Notice

The information contained in this datasheet shall in no event be regarded as a guarantee of conditions or characteristics. This product has to be used within its specified maximum ratings, and is subject to customer's compliance with any applicable legal requirement, norms and standards.

Except as otherwise explicitly approved by Mitsubishi Electric Corporation in a written document signed by authorized representatives of Mitsubishi Electric Corporation, our products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

In usage of power semiconductor, there is always the possibility that trouble may occur with them by the reliability lifetime such as Power Cycle, Thermal Cycle or others, or when used under special circumstances (e.g. condensation, high humidity, dusty, salty, highlands, environment with lots of organic matter / corrosive gas / explosive gas, or situations which terminals of semiconductor products receive strong mechanical stress). Therefore, please pay sufficient attention to such circumstances. Further, depending on the technical requirements, our semiconductor products may contain environmental regulation substances, etc. If there is necessity of detailed confirmation, please contact our nearest sales branch or distributor.

The contents or data contained in this datasheet are exclusively intended for technically trained staff. Customer's technical departments should take responsibility to evaluate the suitability of Mitsubishi Electric Corporation product for the intended application and the completeness of the product data with respect to such application. In the customer's research and development, please evaluate it not only with a single semiconductor product but also in the entire system, and judge whether it's applicable. As required, pay close attention to the safety design by installing appropriate fuse or circuit breaker between a power supply and semiconductor products to prevent secondary damage. Please also pay attention to the application note and the related technical information.

Keep safety first in your circuit designs!

Mitsubishi Electric Corporation puts the maximum effort into making semiconductor products better and more reliable, but there is always the possibility that trouble may occur with them. Trouble with semiconductors may lead to personal injury, fire or property damage. Remember to give due consideration to safety when making your circuit designs, with appropriate measures such as (i) placement of substitutive, auxiliary circuits, (ii) use of non-flammable material or (iii) prevention against any malfunction or mishap.

Notes regarding these materials

- These materials are intended as a reference to assist our customers in the selection of the Mitsubishi Electric Semiconductor product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Mitsubishi Electric Corporation or a third party.
- Mitsubishi Electric Corporation assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.
- All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Mitsubishi Electric Corporation without notice due to product improvements or other reasons. It is therefore recommended that customers contact Mitsubishi Electric Corporation or an authorized Mitsubishi Electric Semiconductor product distributor for the latest product information before purchasing a product listed herein.
The information described here may contain technical inaccuracies or typographical errors. Mitsubishi Electric Corporation assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors.
Please also pay attention to information published by Mitsubishi Electric Corporation by various means, including the Mitsubishi Electric Semiconductor home page (<http://www.MitsubishiElectric.com/semiconductors/>).
- When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Mitsubishi Electric Corporation assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.
- Mitsubishi Electric Corporation semiconductors are not designed or manufactured for use in a device or system that is used under circumstances in which human life is potentially at stake. Please contact Mitsubishi Electric Corporation or an authorized Mitsubishi Electric Semiconductor product distributor when considering the use of a product contained herein for any specific purposes, such as apparatus or systems for transportation, vehicular, medical, aerospace, nuclear, or undersea repeater use.
- The prior written approval of Mitsubishi Electric Corporation is necessary to reprint or reproduce in whole or in part these materials.
- If these products or technologies are subject to the Japanese export control restrictions, they must be exported under a license from the Japanese government and cannot be imported into a country other than the approved destination.
Any diversion or re-export contrary to the export control laws and regulations of Japan and/or the country of destination is prohibited.
- Please contact Mitsubishi Electric Corporation or an authorized Mitsubishi Electric Semiconductor product distributor for further details on these materials or the products contained therein.

Generally the listed company name and the brand name are the trademarks or registered trademarks of the respective companies.