

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty

产品规格

Compliances
Certifications
Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Mounting method
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fitted with:
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Connection
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application

Date

Voltage type
Packaging type
Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse

170M2767

051712254489

75 mm

77 mm

163 mm

212.2 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

200 kAIC

64 mm

No

AC

DIN 43 620 Flush

200 A

Flush end 00BTN/60 Type T indicator for micro

IEC 60269-4 flush end connections type A

Type T Indicator for micro

00

690 V (IEC)

Top fuse status indicator

23000 at 660 V

690 V

None

Blade end x blade end

M8

aR (accompanied semiconductor protection)

35 W

Fuse

Square body, flush end contacts

200 kA

Class aR

3400

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard