

**常用规格**

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty

**产品规格**

Compliances  
Certifications  
Interrupt rating  
Center-to-center distance of connections  
Insulated metal gripping lugs (IMGL)  
Current type  
Mounting method  
Amperage Rating  
Fuse type  
Fuse system (according to IEC 60269)  
Fitted with:  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Rated voltage AC  
Color  
Connection  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Class  
Pre arc (I2T)  
Application

**Date**

Voltage type  
Packaging type  
Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse

170M2768

051712254496

75 mm

77 mm

163 mm

247.4 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

64 mm

No

AC

DIN 43 620 Flush

250 A

Flush end 00BTN/60 Type T indicator for micro

IEC 60269-4 flush end connections type A

Type T Indicator for micro

00

690 V (IEC)

Top fuse status indicator

42000 at 660 V

690 V

None

Blade end x blade end

M8

aR (accompanied semiconductor protection)

645 W

Fuse

Square body, flush end contacts

200 kA

Class aR

6250

Semiconductor, DC Common bus, DC drives, power  
converters/rectifiers

Standard