

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances

产品规格

Certifications
Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Mounting method
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Connection
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application
Voltage type
Packaging type
Date
Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse
170M2708
051712254281
64 mm
62 mm
30 mm
211 g
Not Applicable
CE Marked RoHS Compliant
UL Recognized IEC Rated
200 kAIC

No
AC
DIN 43 620 Flush
25 A
Flush end 00B/60 Visual indicator
IEC 60269-4 flush end connections type A
00
690 V (IEC)
Top fuse status indicator

130 at 660 V
690 V
None
Blade end x blade end
M8
gR (general purpose semiconductor protection)
6 W
Fuse
Square body, flush end contacts
200 kA
Class gR
19
semiconductor protection

Standard