

**常用规格**

Product Name  
Catalog Number  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Compliances

**产品规格**

Certifications  
Rated voltage DC  
Interrupt rating  
Center-to-center distance of connections  
Current type  
Release characteristic  
Amperage Rating  
Frequency rating - max  
Fuse system (according to IEC 60269)  
Rated switching capacity  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I<sup>2</sup>T)  
Color  
Material  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Frequency rating - min  
Class  
Pre arc (I<sup>2</sup>T)  
Application  
Voltage type  
Packaging type  
Date  
Mon Oct 23 2023

Eaton Bussmann series high speed traction fuse

170M2015

131 mm

88 mm

75 mm

2125 g

CE RoHS

IEC 60269-4

750 V

110 kAIC

129 mm

DC

Other

750 A

62 Hz

IEC 60269-4 flush end connections type A

110 A

3

1275000 at 750 Vdc

None

Ceramic

gR (general purpose semiconductor protection)

167 W

Fuse

Square body, flush end contacts

110 kA

45 Hz

Class gR

307600

traction third rail

Standard