

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty  
Compliances

产品规格

Certifications  
Interrupt rating  
Clearing loss  
Center-to-center distance of connections  
Insulated metal gripping lugs (IMGL)  
Current type  
Amperage Rating  
Fuse type  
Fuse system (according to IEC 60269)  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Rated voltage AC  
Color  
Connection  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Class  
Pre arc (I2T)  
Application

Date

Voltage type  
Packaging type  
Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse

170M3068

051712254731

305 mm

65 mm

145 mm

310 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

55

78 mm

No

AC

350 A

DIN 43653 TN/80 Type T Indicator for Micro

Other

1\*

690 V (IEC), 700 V (UL)

Top fuse status indicator

68500 at 660 V

690 V

None

Blade end x blade end

M10

aR (accompanied semiconductor protection)

55 W

Fuse

Square body, slotted center bolted tags

200 kA

Class aR

10000

Semiconductor, DC Common bus, DC drives, power  
converters/rectifiers

Standard