

**常用规格**

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty

**产品规格**

Compliances  
Certifications  
Interrupt rating  
Clearing loss  
Center-to-center distance of connections  
Insulated metal gripping lugs (IMGL)  
Current type  
Amperage Rating  
Fuse type  
Fuse system (according to IEC 60269)  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Rated voltage AC  
Color  
Connection  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Class  
Pre arc (I2T)  
Application

**Date**

Voltage type  
Packaging type  
Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse

170M3209

051712255165

305 mm

65 mm

145 mm

341 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

200 kAIC

11

108 mm

No

AC

50 A

DIN 43653 TN/110 Type T Indicator for Micro

Bolted tag

Other

1\*

690 V (IEC), 700 V (UL)

Top fuse status indicator

515 at 660 V

690 V

None

Blade end x blade end

M10

aR (accompanied semiconductor protection)

11 W

Fuse

Square body, slotted center bolted tags

200 kA

Class aR

77

Semiconductor, DC Common bus, DC drives, power  
converters/rectifiers

Standard