

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty

产品规格

Compliances  
Certifications  
Interrupt rating  
Center-to-center distance of  
connections  
Insulated metal gripping lugs (IMGL)  
Current type  
Amperage Rating  
Fuse type  
Fuse system (according to IEC 60269)  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Rated voltage AC  
Color  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Class  
Pre arc (I2T)

Date

Application  
Voltage type  
Packaging type  
Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse

170M3966

051712678889

290 mm

62 mm

142 mm

0.001 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

125 kAIC

106 mm

No

AC

63 A

DIN 43653 KN/110 Type K Indicator for Micro

Other

1\*

1000 V (IEC)

Centre fuse status indicator

1300 at 1000 V

1000 V

None

M10

aR (accompanied semiconductor protection)

25 W

Fuse

Square body, slotted center bolted tags

125 kA

Class aR

215

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Standard