

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Compliances
Certifications
Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Mounting method
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fitted with:
Fuse size
Voltage rating
Fuse indicator
Construction size
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application
Voltage type
Packaging type

产品规格

Date

Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse

170M3448

051712256193

92 mm

60 mm

163 mm

0.885 g

RoHS Compliant EAC CE

IEC 60269-4 UL 248-13

100 kAIC

87.6 mm

No

AC

Flush

400 A

Flush end BKN/80 Type K Indicator for Micro

IEC 60269-4 flush end connections type A

Type K Indicator for micro

1*

1250 V (IEC), 1300 V (UL)

Centre fuse status indicator

Other

1250 V

None

M8

aR (accompanied semiconductor protection)

70 W

Fuse

Square body, flush end contacts

100 kA

Class aR

53000

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard