

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty

产品规格

Compliances  
Certifications  
Interrupt rating  
Center-to-center distance of  
connections  
Insulated metal gripping lugs (IMGL)  
Current type  
Amperage Rating  
  
Fuse type  
Fuse system (according to IEC 60269)  
Fitted with:  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Rated voltage AC  
Color  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Class  
Pre arc (I2T)  
  
Application  
  
Voltage type  
Packaging type  
Date  
Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse

170M3364

051712812122

210 mm

80 mm

160 mm

705 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

76 mm

No

AC

160 A

French style EKN/Type K Indicator for Micro

Bolted tag

Other

Type K Indicator for micro

1\*

690 V

Centre fuse status indicator

7500 at 660 V

None

M8

aR (accompanied semiconductor protection)

30 W

Fuse

Square body, slotted center bolted tags

200 kA

Class aR

1100

Semiconductor, DC Common bus, DC drives, power  
converters/rectifiers

Standard