

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty

产品规格

Compliances  
Certifications  
Interrupt rating  
Center-to-center distance of connections  
Insulated metal gripping lugs (IMGL)  
Current type  
Mounting method  
Amperage Rating  
Fuse type  
Fuse system (according to IEC 60269)  
Fitted with:  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Rated voltage AC  
Color  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Class  
Pre arc (I2T)  
Application

Date

Voltage type  
Packaging type  
Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse

170M3393

051712255905

96 mm

50 mm

170 mm

202 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

100 kAIC

74 mm

No

AC

Flush

160 A

Flush end BKN/75 Type K Indicator for Micro

IEC 60269-4 flush end connections type A

Type K Indicator for micro

1\*

1250 V (IEC), 1300 V (UL)

Centre fuse status indicator

Other

16000 at 1000 V, 21000 at 1250 V

1250 V

None

M8

aR (accompanied semiconductor protection)

30 W

Fuse

Square body, flush end contacts

100 kA

Class aR

2600

Semiconductor, DC Common bus, DC drives, power  
converters/rectifiers

AC/DC

Standard