

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty

产品规格

Compliances
Certifications
Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Mounting method
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fitted with:
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application

Date

Voltage type
Packaging type
Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse
170M3465
051712799232
60 mm
50 mm
43 mm
266 g
Not Applicable
CE Marked RoHS Compliant
UL Recognized IEC Rated
200 kAIC

No
AC
Flush
200 A
Flush end BKN/Type K Indicator for Micro
IEC 60269-4 flush end connections type A
Type K Indicator for micro
1*
690 V (IEC), 700 V (UL)
Centre fuse status indicator
Other
15000 at 660 V
690 V
None
M8
aR (accompanied semiconductor protection)
35 W
Fuse
Square body, flush end contacts
200 kA
Class aR
2200
Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard