

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty

产品规格

Compliances
Certifications
Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating

Fuse type

Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)

Date

Application

Voltage type
Packaging type
Tue Oct 24 2023

Eaton Bussmann series high speed square body fuse

170M3982

051712678988

305 mm

65 mm

145 mm

458 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

125 kAIC

108 mm

No

AC

63 A

DIN 43653 TN/110 Type T Indicator for Micro

Bolted tag

Other

1*

1000 V (IEC)

Top fuse status indicator

1300 at 1000 V

1000 V

None

M10

aR (accompanied semiconductor protection)

25 W

Fuse

Square body, slotted center bolted tags

125 kA

Class aR

215

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Standard