

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty

产品规格

Compliances
Certifications
Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)

Date

Application
Voltage type
Packaging type
Tue Oct 24 2023

Eaton Bussmann series high speed square body fuse

170M3967

051712678896

290 mm

62 mm

142 mm

0.9 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

125 kAIC

106 mm

No

AC

80 A

DIN 43653 KN/110 Type K Indicator for Micro

Other

1*

1000 V (IEC)

Centre fuse status indicator

2750 at 1000 V

1000 V

None

M10

aR (accompanied semiconductor protection)

30 W

Fuse

Square body, slotted center bolted tags

125 kA

Class aR

460

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Standard