

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty

产品规格

Compliances
Certifications
Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fitted with:
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application
Voltage type
Packaging type
Date
Tue Oct 24 2023

Eaton Bussmann series high speed square body fuse

170M3366

051712255790

168 mm

80 mm

124 mm

705 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

76 mm

No

AC

250 A

French style EKN/Type K Indicator for Micro

Bolted tag

Other

Type K Indicator for micro

1*

690 V

Centre fuse status indicator

28500 at 660 V

None

M8

aR (accompanied semiconductor protection)

40 W

Fuse

Square body, slotted center bolted tags

200 kA

Class aR

4200

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard