

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Compliances

产品规格

Certifications
Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fitted with:
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)

Date

Application
Voltage type
Packaging type
Tue Oct 24 2023

Eaton Bussmann series high speed square body fuse

170M3535

051712678599

43 mm

60 mm

111 mm

464 g

RoHS Compliant EAC CE

IEC 60269-4

125 kAIC

116 mm

No

AC

125 A

US Style FKE/115 Type K indicator for micro

Other

Type K Indicator for micro

1*

1000 V

Top fuse status indicator

8600 at 1000 V

None

M10

aR (accompanied semiconductor protection)

40 W

Fuse

Square body, center bolted tags

125 kA

Class aR

8600

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard