

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty

产品规格

Compliances
Certifications
Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Mounting method
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fitted with:
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application

Date

Voltage type
Packaging type
Tue Oct 24 2023

Eaton Bussmann series high speed square body fuse

170M3488

051712256230

96 mm

50 mm

170 mm

186 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

100 kAIC

74 mm

No

AC

Flush

50 A

Flush end GKN/75 Type K indicator for micro

IEC 60269-4 flush end connections type A

Type K Indicator for micro

1*

1250 V (IEC), 1300 V (UL)

Centre fuse status indicator

Other

815 at 1000 V, 1100 at 1250 V

1250 V

None

aR (accompanied semiconductor protection)

15 W

Fuse

Square body, flush end contacts

100 kA

Class aR

135

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard