

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty

产品规格

Compliances
Certifications
Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating

Fuse type

Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)

Date

Application

Voltage type
Packaging type
Wed Oct 25 2023

Eaton Bussmann series high speed square body fuse

170M3192

051712255080

305 mm

65 mm

145 mm

72 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

100 kAIC

108 mm

No

AC

125 A

DIN 43653 TN/110 Type T Indicator for Micro

Bolted tag

Other

1*

1250 V (IEC), 1300 V (UL)

Top fuse status indicator

9000 at 1000 V, 11500 at 1250 V

1250 V

None

M10

aR (accompanied semiconductor protection)

35 W

Fuse

Square body, slotted center bolted tags

100 kA

Class aR

1450

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Standard